

HIWATT

Specifications

Model No.	504	103
Output power, RMS*	50 watts	100 watts
Total Peak, RMS	125 watts	250 watts
Pre-amp valves	4xECC83	4xECC83
Output valves	2xEL34	4xEL34
Fuses, Mains***	3A standard	3A standard
H.T.	1A standard	3A standard
Dimensions	11x25x10½"	11x25x10½"
Weight	20 Kilos	21 Kilos

*Into standard load impedances, i.e. 4, 8, or 16 ohms

***When used on 105v & 115v tapping mains fuse value is doubled.

The following specifications are common to all the amplifiers:

Input impedance:	1 m Ohm
Input sensitivity:	2.5mV RMS measured at 500Hz
Tone controls:	Bass ± 20 db, Treble -6 to $+30$ db (including presence), Middle $+10$ db.
Controls:	Normal volume, Bright volume, Bass, Treble, Middle, Presence, Master volume, Mains on/off, Standby on/off.
Inputs:	1 x Normal, 1 x Bright.
Rear Panel:	Output Impedance adjustment, 4, 8, 16 ohm

Warranty

1 year parts and labor (except tubes 90 days).

We reserve the right to change specifications without notice for product improvements.

Sterling Imports Ltd.
700 Scenic Drive
Modesto, California 95350 U.S.A.
(209) 578-4277